

## General purpose Tank cleaner & degreaser

### FEATURES & BENEFITS

- Approved according to IMO MEPC.1/Circ. 590
- Suitable for use on almost all tank linings
- Controlled emulsion breakage-allows cleaned oil to be easily reclaimed
- Contains a blend of solvents and emulsifiers formulated to provide a broad spectrum cleaner with maximum solvent penetration and efficient emulsification.

### DESCRIPTION

- NAVACLEAN 818—COLDWASH may be hand-sprayed undiluted for spot cleaning of petroleum oil residues, petroleum based chemicals and some natural oils
- Emulsifying agents then enable the residues to be easily removed by fresh or salt water
- NAVACLEAN 818—COLDWASH is available in 25/200/208 litre drums.

## NAVACLEAN 818 COLDWASH

For detailed instructions on tank cleaning please contact us at NAVADAN.  
A range of support application equipment is also available.



### Product Information: NAVACLEAN 818 COLDWASH

NAVADAN APS · Skruengangen 3 · 2690 Karlslunde · Denmark  
Tel. +45 4917 0357 · E-mail: [navadan@navadan.com](mailto:navadan@navadan.com) · [www.navadan.com](http://www.navadan.com)

## DIRECTIONS FOR USE/APPLICATIONS & DOSAGE RATES

Undiluted NAVACLEAN 818 - COLDWASH is recommended for local cleaning and degreasing and may be applied by brush, hand-spray, immersion soaking or any other conventional means. Depending on the type and the amount of residue to be removed it may be necessary to allow up to 6 hours for the cleaner to react before rinsing with either fresh or salt water.

NAVACLEAN 818 - COLDWASH may also be used by injection or recirculation at strengths up to 5%, at a temperature of 60-80 °C.

For specific cleaning instructions please contact NAVADAN.

## Product Characteristics

Appearance: Clear Amber liquid

Specific gravity: 0.83

Flash Point (PMCC): > 62 °C

pH-value at 20°C: 8

Corrosive action:

- Metals: None
- Rubber: Slight swelling

**For Nature of special risks & safety regulations, please see our Material Safety Data Sheet**



The information and recommendations given herein are believed to be accurate and reliable. However, since conditions of actual use are beyond our control, any recommendations or suggestions are made without any warranty and liability, expressed or implied.



**Product Information: NAVACLEAN 818 COLDWASH**

NAVADAN APS · Skruengangen 3 · 2690 Karlslunde · Denmark  
Tel. +45 4917 0357 · E-mail: [navadan@navadan.com](mailto:navadan@navadan.com) · [www.navadan.com](http://www.navadan.com)