

Acid based rust remover & metal brightner

FEATURES & BENEFITS

- Approved according to IMO MEPC.1/Circ. 590
- Removal of white residues/stains/salt deposits on tank coating
- Polishing of stainless steel tanks.

DESCRIPTION

- NAVACLEAN 873 - RUST & STAIN REMOVER is designed to remove the white stains or residues that can appear in cargo tanks after cargoes such as: Stearin, olein, palm oil, and PFAD.
- On some coatings, washing with hot sea water after discharge of caustic or different lye cargoes, may result in white stains, or stripes on tank surfaces
- NAVACLEAN 873 – RUST & STAIN REMOVER can be used to remove these white stains/stripes
- NAVACLEAN 873 – RUST & STAIN REMOVER is available in 200/208 litre drums.

NAVACLEAN 873 RUST & STAIN REMOVER

For detailed instructions on tank cleaning please contact us at NAVADAN.
A range of support application equipment is also available.



Product Information: NAVACLEAN 873 RUST & STAIN REMOVER

NAVADAN APS · Skrugangen 3 · 2690 Karlslunde · Denmark
Tel. +45 4917 0357 · E-mail: navadan@navadan.com · www.navadan.com

DIRECTIONS FOR USE/APPLICATIONS & DOSAGE RATES

Inject 0.5 litre of NAVACLEAN 874 – RS BASIC for every 100 ltrs of washing water, directly into tank washing system (Butterworth system). Wash each tank for approx. 20-30 minutes (1 washing cycle). Recommended temperature of washing water is 75 - 80°C. Finally rinse each tank with fresh water

Caution: Always add NAVACLEAN 873 - RUST & STAIN REMOVER to water.
NAVACLEAN 873 - RUST & STAIN REMOVER should not be used on galvanised, or tinned surfaces.

PRODUCT CHARACTERISTICS

Appearance:	Clear liquid
Specific gravity:	1.22 at 20°C
Flash Point:	None
pH-value (1% solution):	2
Corrosive action:	
• Metals:	Slight action
• Rubber:	None

For Nature of special risks & safety regulations, please see our Material Safety Data Sheet



The information and recommendations given herein are believed to be accurate and reliable. However, since conditions of actual use are beyond our control, any recommendations or suggestions are made without any warranty and liability, expressed or implied.